

## Seicane S127302 2005-2009 Ford Mustang aftermarket radio dvd gps stereo upgrade installation replacement instruction

Seicane S127302 2005-2009 Ford Mustang head unit after installation



**Please note:**

**This unit can be suitable for the following cars which are also with the same installation steps as follows.**

- 2005-2009 Ford Mustang
- 2007-2010 Ford Expedition
- 2004-2014 Ford F150 F250 F350
- 2007-2010 Ford Expedition ( U324 )
- 2007-2010 Ford Expedition EL/Max(U354)
- 2006-2009 Ford Fusion 4-door Sedan
- 2006-2010 Ford Explorer(U251)
- 2006-2009 Ford Fusion
- 2005-2007 Ford 500
- 2004-2006 Ford Focus
- 2007-2009 Ford Edge
- 2008-2009 Ford Escape
- 2005-2009 Ford Freestyle
- 2005-2006 Mercury Montego
- 2007-2009 Mercury Mountaineer

**Tips about the installation:**

1. Please disconnect the power before the installation.
2. Please prepare a lever and a screwdriver before the removal and the installation.
3. Please keep all the separate parts from the car. Please take great care of the dashboard to avoid scratching it during its detachment and installation. Please keep handy any parts from the car and make use of all the original screws from the car as much as possible. so each related part of the unit can be fixed securely.
4. For your convenience, here's the recommended tools for removal and installation from Seicane, please check for more details: <http://www.seicane.com/car-dvd-dismantling-device-srd-400>

## 2005-2009 Ford Mustang head unit installation guide

Step 1: Remove the trim around gear shifter.



Step 2: Remove screws securing center console lid with a screwdriver.



Step 3: Remove the center console trim.



Step 4: Remove console side panels on both driver and passenger sides.



Step 5: Remove bolts securing radio bezel and AC controls.



Step 6: Unplug AC controls (from passenger side).



Step 7: Remove the radio bezel and AC controls.



Step 8: Remove screws securing radio to the vehicle, and take the original radio out of the dash.



Step 9: Check all the accessories for the new Seicane head unit.



Step 10: Connect the harnesses to the back of the new Seicane head unit.



Step 11: Connect the Seicane head unit to your original car radio 's plugs, and put the new Seicane head unit into the dash.

Step 12: Turn on the new Seicane head unit and check whether the radio is working properly.

Step 13: Install all screws, trims, panels, bolts and the radio bezel and AC controls into their original place.